

Model 1000CW



Double Door, Upright, Outdoor Ice Merchandiser

| Model | Dimensions D x W x H | Volts / Hertz / Phase | Amps | Unit H.P. | Refrigerant | Capacity (Cu. Ft.) | Shipping Weight (lbs.) |
|--------|--|-----------------------|-------------------------------|--------------|-------------|-----------------------|---------------------------|
| 1000CW | Ext. 35" x 94" x 79" Int. 31" x 90" x 59" | 115V / 60HZ / 1PH | 6.3 amps / 15- amp circuit | 1/2 | R448A | 95 | 545 |

Agency Listings

- ETL Listed in accordance to UL471 10th Edition Standard

Connections

- Electrical connection: Heavy Duty 12-Gauge 10-Foot Cord with plug

Optional Feature

- Bright Aluminum Diamond Plate Kick Plate
- Door Opening Ice Breaker Bar
- 4" Casters with 1/4 " Aluminum Angle Perimeter Frame
- TX Valve Metering Device
- ETL Listed in accordance to NSF7 Standard

Standard Features

- Merchandiser designed to hold product between 10°F to 20°F
- 26-gauge Ceram-A-Star pre-painted steel exterior/26-gauge galvanized steel interior
- Solid Insulated Door with TPE Magnetic, Positive Seal, Self-Closing Gasket
- Top Mounted Refrigeration System with Low Global Warming Potential
- Copper Tube in Wall Evaporator with Capillary Tube (Cold Wall)
- Ecomate® foamed-in-place insulation: VOC-compliant, EPA Approved, No Ozone Depletion, No Global Warming, Environmentally Friendly, Thermally Efficient
- Electronic Control System Gives Service Friendly Fault Codes
- Floor Racks
- Solid Injection Molded Feet