Model 300CWG









Single Door, Upright, Indoor Ice Merchandiser

Model	Dimensions D x W x H	Volts / Hertz / Phase	Amps	Unit H.P.	Refrigerant	Capacity (Cu. Ft.)	Shipping Weight (lbs.)
300CWG	Ext. 30" x 36" x 79" Int. 26" x 32" x 59"	115V / 60HZ / 1PH	4.25 amps / 15-amp circuit	1/4	R448A	30	315

Agency Listings

ETL Listed in accordance to UL471 10th Edition Standard

Connections

- Electrical connection: Heavy Duty 12-Gauge 10-Foot. Cord with plug
- > Condensation Plumbing Connection: 1/2" I.D. Plastic

Optional Feature

- ➤ 24" LED Light
- > Bright Aluminum Diamond Plate Kick Plate
- > Door Opening Ice Breaker Bar
- > 4" Casters with 1/4 " Aluminum Angle Perimeter Frame
- > TX Valve Metering Device
- > ETL Listed in accordance to NSF7 Standard
- > Shelves

Standard Features

- Merchandiser designed to hold product between 10°F to 20°F
- 26-gauge Ceram-A-Star pre-painted steel exterior/26-gauge galvanized steel interior
- Solid Insulated Door with TPE Magnetic, Positive Seal, Self-Closing Gasket
- Top Mounted Refrigeration System with Low Global Warming Potential
- Copper Tube In Wall Evaporator with Capillary Tube -Cold Wall (CW)
- Ecomate® foamed-in-place insulation: VOC-compliant, EPA Approved, No Ozone Depletion, No Global Warming, Environmentally Friendly, Thermally Efficient
- Electronic Control System Gives Service Friendly Fault Codes
- > Floor Racks
- > Solid Injection Molded Feet