

Model 600AD



Outdoor, Slant Front, Double Solid Doors Ice Merchandiser

Model	Dimensions D x W x H	Volts / Hertz / Phase	Amps	Unit H.P.	Refrigerant	Capacity (Cu. Ft.)	Shipping Weight (lbs.)
600AD	Ext. 35" x 70.25" x 72" Int. 31" x 66.25" x 53"	115V / 60HZ / 1PH	6.84 amps / 15-amp circuit	1/3	R448A	60	435

Agency Listings

- ETL Listed in accordance to UL471 10th Edition Standard

Connections

- Electrical connection: Heavy Duty 12-Gauge 10-Foot. Cord with plug
- Condensation Plumbing Connection: 1/2" I.D. Plastic Tube

Optional Feature

- Bright Aluminum Diamond Plate Kick Plate
- Door Opening Ice Breaker Bar
- 4" Casters with 1/4" Aluminum Angle Perimeter Frame
- TX Valve Metering Device
- ETL Listed in accordance to NSF7 Standard

Standard Features

- Merchandiser designed to hold product between 10°F to 20°F
- 26-gauge Ceram-A-Star pre-painted steel exterior/26-gauge galvanized steel interior
- Solid Insulated Door with TPE Magnetic, Positive Seal, Self-Closing Gasket
- Top Mounted Refrigeration System with Low Global Warming Potential
- Copper Tube Evaporator with Capillary Tube
- Ecomate® foamed-in-place insulation: VOC-compliant, EPA Approved, No Ozone Depletion, No Global Warming, Environmentally Friendly, Thermally Efficient
- Electronic Control System Gives Service Friendly Fault Codes
- Electric Automatic Defrost System (AD)
- Floor Racks
- Solid Injection Molded Feet