

Model 670AD



Double Door, Upright, Outdoor Ice Merchandiser

| Model | Dimensions D x W x H | Volts / Hertz / Phase | Amps | Unit H.P. | Refrigerant | Capacity (Cu. Ft.) | Shipping Weight (lbs.) |
|-------|--|-----------------------|-------------------------------|--------------|-------------|-----------------------|---------------------------|
| 670AD | Ext. 35" x 62" x 79" Int. 31" x 58" x 59" | 115V / 60HZ / 1PH | 6.5 amps / 15- amp circuit | 1/3 | R448A | 61 | 440 |

Agency Listings

- ETL Listed in accordance to UL471 10th Edition Standard

Connections

- Electrical connection: Heavy Duty 12-Gauge 10-Foot Cord with plug
- Condensation Plumbing Connection: 1/2" I.D. Plastic Tube

Optional Feature

- 24" LED Light
- Bright Aluminum Diamond Plate Kick Plate
- Door Opening Ice Breaker Bar
- Electric Condensation Pan
- 4" Casters with 1/4" Aluminum Angle Perimeter Frame
- TX Valve Metering Device
- ETL Listed in accordance to NSF7 Standard
- Shelves

Standard Features

- Merchandiser designed to hold product between 10°F to 20°F
- 26-gauge Ceram-A-Star pre-painted steel exterior/26-gauge galvanized steel interior
- Solid Insulated Door with TPE Magnetic, Positive Seal, Self-Closing Gasket
- Top Mounted Refrigeration System with Low Global Warming Potential
- Aluminum Fin/Copper Tube Evaporator with Capillary Tube
- Ecomate® foamed-in-place insulation: VOC-compliant, EPA Approved, No Ozone Depletion, No Global Warming, Environmentally Friendly, Thermally Efficient
- Electronic Control System Gives Service Friendly Fault Codes
- Electric Automatic Defrost (AD) System
- Floor Racks
- Solid Injection Molded Feet