

# Model 850CW



## Double Door, Upright, Outdoor Ice Merchandiser

Model	Dimensions D x W x H	Volts / Hertz / Phase	Amps	Unit H.P.	Refrigerant	Capacity (Cu. Ft.)	Shipping Weight (lbs.)
850CW	Ext. 35" x 84" x 79" Int. 31" x 80" x 59"	115V / 60HZ / 1PH	6.2 amps / 15-amp circuit	1/2	R448A	85	475

### Agency Listings

- ETL Listed in accordance to UL471 10th Edition Standard

### Connections

- Electrical connection: Heavy Duty 12-Gauge 10-Foot Cord with plug

### Optional Feature

- 24" LED Light
- Bright Aluminum Diamond Plate Kick Plate
- Door Opening Ice Breaker Bar
- 4" Casters with 1/4" Aluminum Angle Perimeter Frame
- TX Valve Metering Device
- ETL Listed in accordance to NSF7 Standard
- Shelves

### Standard Features

- Merchandiser designed to hold product between 10°F to 20°F
- 26-gauge Ceram-A-Star pre-painted steel exterior/26-gauge galvanized steel interior
- Solid Insulated Door with TPE Magnetic, Positive Seal, Self-Closing Gasket
- Top Mounted Refrigeration System with Low Global Warming Potential
- Copper Tube in Wall Evaporator with Capillary Tube (Cold Wall)
- Ecomate® foamed-in-place insulation: VOC-compliant, EPA Approved, No Ozone Depletion, No Global Warming, Environmentally Friendly, Thermally Efficient
- Electronic Control System Gives Service Friendly Fault Codes
- Floor Racks
- Solid Injection Molded Feet